embertec[®] SmartSwitch[®] AV

Ouick Installation Guide Embertec SmartSwitch™



- 1. Switch off the power at the wall socket and unplug your appliances from the wall socket.
- 2. Identify equipment that requires constant power for timers, program guides and recording features, and plug them into the socket marked 'Always On', or another wall socket. A powerboard may be plugged into the 'Always On' socket.
- **3.** Plug your AV equipment that can be automatically switched off into a powerboard (powerboard not supplied).
- **4.** Connect the powerboard to the 'Power Saver' socket.
- 5. Connect the supplied SmartSensor cable to the underside of the Embertec SmartSwitch™ AV and make sure that it fits securely in the socket.
- **6.** Place the SmartSensor in a convenient location that is in line of sight. Close to your television is the best position, and within normal operation of your existing remote control(s).
- 7. Plug the Embertec SmartSwitch™ AV into a 230V or 240V power point, and turn the power point on at the wall. (This is the standard power in all Australian homes).
- 8. The LED monitoring light on the Embertec SmartSwitch™ AV will now light up for 3 seconds to indicate detection of connected equipment. This also indicates the Embertec SmartSwitch™ AV is monitoring your power consumption and providing power to the 'Power Saver' socket.
- **9.** Now turn on your equipment as normal.



embertec[®] SmartSwitch[™] AV

